



FULL-SIZE HYDROSTATIC OR SHUTTLE SHIFT TRACTORS.



- 2,700 lbs loader lifting capacity at the pins
- Skid steer compatible front end loader
- Cabs feature upgraded heated seats and premium Alpine entertainment systems
- Durable cast iron transmissions and axles





**48HP AND 55HP MODELS ARE
AVAILABLE WITH SHUTTLE SHIFT OR
HYDROSTATIC TRANSMISSIONS,
OPEN OR CAB CONFIGURATIONS.**

50 SERIES

48 HP MODEL	MODEL NAME	5045S	5045H	5045CS	5045CH
DIMENSION					
	OVERALL LENGTH, IN (MM), 3P	127.4 (3,236)	127.4 (3,236)	127.4 (3,236)	127.4 (3,236)
	OVERALL WIDTH, IN (MM)	64.9 (1,650)	64.9 (1,650)	64.9 (1,650)	64.9 (1,650)
	HEIGHT TO TOP OF ROPS, IN (MM)	98.4 (2,500)	98.4 (2,500)	97 (2,463)	97 (2,463)
	WHEELBASE, IN (MM)	71.1 (1,806)	71.1 (1,806)	71.1 (1,806)	71.1 (1,806)
	MIN. GROUND CLEARANCE, IN (MM)	15.5 (394)	15.5 (394)	15.5 (394)	15.5 (394)
	WEIGHT, LB (KG)	3,831 (1,738)	3,831 (1,738)	4,349 (1,973)	4,349 (1,973)
PTO	540, 540E	584, 791	584, 791	584, 791	584, 791
HYDROSTATIC					
	MAXIMUM TOTAL FLOW, GPM (CC/REV)	16.4 (62.1)	15.7 (59.4)	16.4 (62.1)	15.7 (59.4)
	IMPLEMENT PUMP CAP, GPM (CC/REV)	11.4 (43.2)	10.7 (40.5)	11.4 (43.2)	10.7 (40.5)
	STEERING PUMP CAP, GPM (CC/REV)	5 (18.9)	5 (18.9)	5 (18.9)	5 (18.9)
	3P CATEGORY (1 / 2 / 3)	1	1	1	1
	HITCH LIFT CAPACITY, LB (KG)	3306 (1,500)	3306 (1,500)	3306 (1,500)	3306 (1,500)
	AT 24 INCHES BEHIND LINK ENDS, LB (KG)	2425 (1,100)	2425 (1,100)	2425 (1,100)	2425 (1,100)
ENGINE					
	MODEL	A2300N2-UTR_4	A2300N2-UTR_4	A2300N2-UTR_4	A2300N2-UTR_4
	FUEL SYSTEM	WATER-COOLED DIESEL	WATER-COOLED DIESEL	WATER-COOLED DIESEL	WATER-COOLED DIESEL
	DISPLACEMENT, IN (CC)	139.5 (2,286)	139.5 (2,286)	139.5 (2,286)	139.5 (2,286)
	NUMBER OF CYLINDERS	4	4	4	4
	RATED ENGINE POWER, HP (KW)	48 (35.8)	48 (35.8)	48 (35.8)	48 (35.8)
	RATED SPEED, RPM	2600	2600	2600	2600
	MAX PTO POWER, HP (KW)	38.4 (28.6)	38.4 (28.6)	38.4 (28.6)	38.4 (28.6)
	DPF / SCR / DOC	DPF /	DOC DPF / DOC	DPF / DOC	DPF / DOC
TRANSMISSION					
	TYPE	SYNCHRO	HST	SYNCHRO	HST
	NUMBER OF GEARS	16F / 16R	4 RANGE	16F / 16R	4 RANGE
55 HP MODEL	MODEL NAME	5055S	5055H	5055CS	5055CH
DIMENSION					
	OVERALL LENGTH, IN (MM), 3P	127.4 (3,236)	127.4 (3,236)	127.4 (3,236)	127.4 (3,236)
	OVERALL WIDTH, IN (MM)	64.9 (1,650)	64.9 (1,650)	64.9 (1,650)	64.9 (1,650)
	HEIGHT TO TOP OF ROPS, IN (MM)	98.4 (2,500)	98.4 (2,500)	97 (2,463)	97 (2,463)
	WHEELBASE, IN (MM)	71.1 (1,806)	71.1 (1,806)	71.1 (1,806)	71.1 (1,806)
	MIN. GROUND CLEARANCE, IN (MM)	15.5 (394)	15.5 (394)	15.5 (394)	15.5 (394)
	WEIGHT, LB (KG)	3,836 (1,740)	3,836 (1,740)	4,349 (1,973)	4,349 (1,973)
PTO	540, 540E	584, 791	584, 791	584, 791	584, 791
HYDROSTATIC					
	MAXIMUM TOTAL FLOW, GPM (CC/REV)	16.4 (62.1)	15.7 (59.4)	16.4 (62.1)	15.7 (59.4)
	IMPLEMENT PUMP CAP, GPM (CC/REV)	11.4 (43.2)	10.7 (40.5)	11.4 (43.2)	10.7 (40.5)
	STEERING PUMP CAP, GPM (CC/REV)	5 (18.9)	5 (18.9)	5 (18.9)	5 (18.9)
	3P CATEGORY (1 / 2 / 3)	1	1	1	1
	HITCH LIFT CAPACITY, LB (KG)	3306 (1,500)	3306 (1,500)	3306 (1,500)	3306 (1,500)
	AT 24 INCHES BEHIND LINK ENDS, LB (KG)	2425 (1,100)	2425 (1,100)	2425 (1,100)	2425 (1,100)
ENGINE					
	MODEL	A2300T3-UTR_4	A2300T3-UTR_4	A2300T3-UTR_4	A2300T3UTR_4
	FUEL SYSTEM	WATER-COOLED DIESEL	WATER-COOLED DIESEL	WATER-COOLED DIESEL	WATER-COOLED DIESEL
	DISPLACEMENT, IN (CC)	139.5 (2,286)	139.5 (2,286)	139.5 (2,286)	139.5 (2,286)
	NUMBER OF CYLINDERS	4	4	4	4
	RATED ENGINE POWER, HP (KW)	55 (41.0)	55 (41.0)	55 (41.0)	55 (41.0)
	RATED SPEED, RPM	2600	2600	2600	2600
	MAX PTO POWER, HP (KW)	44 (32.8)	44 (32.8)	44 (32.8)	44 (32.8)
	DPF / SCR / DOC	DPF / DOC	DPF / DOC	DPF / DOC	DPF / DOC
TRANSMISSION					
	TYPE	SYNCHRO	HST	SYNCHRO	HST
	NUMBER OF GEARS	16F / 16R	4 RANGE	16F / 16R	4 RANGE



www.badboytractors.com
102 Industrial Drive
Batesville, AR 72501

YOUR EXCLUSIVE DEALER:

SPECIFICATIONS SUBJECT TO CHANGE